General

Device Interfaces	Nano SIM card slot, 1x Type C
Display	LCD display (Network type, signal strength, SMS status, operator, battery status, Wi-Fi and security status, Wi-Fi clients)
Buttons	WPS + Power + Reset (hole)

Functionality

Frequency Support[1]	• 5G NR n1/3/20/28/41/77/78 • LTE FDD B1/B3/B5/B7/B8/B20/B28 • LTE TDD B34/38/39/40/41 • WCDMA B1, B8
Wireless IEEE Standard	IEEE 802.11n/g/b/ac/ax[2]
Data Signal Rate	2.4 GHz (up to 286.8 Mbps), 5 GHz (up to 600 Mbps)
Wireless Frequency Range	2.4 - 2.483 GHz, 5.15 - 5.85 GHz
Security Protocol	WPA/WPA2™

Software

Device Management	Touchscreen, Web UI
Software update	Support local update , FOTA

Physical

Power Input	5V / 2A
Battery	Rechargeable 6000 mAh Li-ion battery
Operating Temperature	-10 to 40 ˚C (32 to 131 ˚F)
Storage Temperature	-40 to 70˚ C (-22 to 158 °F)
Operating Humidity	10% to 95% (non-condensing)
Weight	185g
Dimensions	138mm x 71mm x 14.2mm
Certifications	CE

SIM Card Slot

2.01 inch touchscreen

WPS Button

Reset Button

Power Button

5G

Type-C

[1] Mobile broadband speeds will vary and are dependent on a range of factors including network configuration, network capacity, signal strength, and the conditions of your mobile broadband subscription. A 5G subscription is required in order to achieve maximum speeds. [2] Maximum wireless signal rate derived from IEEE Standard 802.11 specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental factors may adversely affect wireless signal range. [3] for more information about compatible mobile service providers, please visit eu.dlink.com for more information.

D-Link®